

Products

Model No.	Bearing Sleeve	Rating Voltage (VAC)	Freq. (HZ)	Rated Current (Amp)	Power Consumption (W)	Speed (RPM)	Air Flow (CFM)	Static Pressure (mm H2O)	Noise (dBA)	Box Pkg. (Pcs)
REC	Ball									



No product available here

80 x 80 x 25 mm

28025 A1 M W		115	50/60	0.12/0.10	12/11	2400/3000	18/22	3.0/3.7	29/30	40
28025 A2 M W		230	50/60	0.7/0.5	13/11	2400/3000	22/25	3.2/4.5	29/30	40



120 x 120 x 38 mm

28038 A1 M T/W		115	50/60	0.21/0.18	18/17	2550/5850	80/105	6.4/7.6	43/48	40
28038 B1 M T/W		115	50/60	0.21/0.18	18/17	2600/2900	85/110	6.4/7.6	43/48	40
28038 A2 M T/W		230	50/60	0.12/0.11	22/20	2550/2850	80/105	6.4/7.6	43/48	40
28038 B2 M T/W		230	50/60	0.12/0.11	22/20	2600/2900	85/110	6.4/7.6	43/48	40



172 x 150 x 51 mm

21725 A1 M W		115	50/60	0.38/0.37	30/29	2500/2800	175/180	12.2/9.7	52/55	20
21725 B1 M W		115	50/60	0.38/0.37	30/29	2600/2900	180/200	12.2/9.7	52/55	20
21725 A1 M W		230	50/60	0.23/0.20	37/35	2500/2800	175/180	12.2/9.7	52/55	20
21725 B2 M W		230	50/60	0.23/0.20	37/35	2600/2900	180/200	12.2/9.7	52/55	20



220 x 60 mm

22060 R B1 W		115	50	0.77	62	2300	360	22	56	10
22060 R B2 W		230	50	0.42	65	2300	360	22	56	10