

Products

Model No.	Bearing Sleeve	Impeller (mm/Angle)	Output Power (Watt)	Rating Voltage (VAC)	Frequency (Hz)	Rated Current (Amp)	Power Consumption (Watt)	Speed (RPM)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Box Pkg. (Pcs)
REC	Ball										



83 x 83 x 13 mm

83-1305 A1		200/28°	5	115	50/60	0.37/0.36	27/25	1300/1500	300	7	20
83-1305 A2		200/28°	5	230	50/60	0.22/0.18	30/28	1300/1500	300	7	20




83 x 83 x 20 mm

83-2007 A1		200/28°	7	115	50/60	0.41/0.40	28/26	1300/1500	300	7	20
		230/22°	7	115	50/60	0.41/0.40	28/26	1300/1500	340	7.5	20
83-2007 A2		200/28°	7	230	50/60	0.24/0.22	34/32	1300/1500	300	7	20
		230/22°	7	230	50/60	0.24/0.22	34/32	1300/1500	340	7.5	20
83-2010 A1		230/22°	10	115	50/60	0.42/0.41	30/28	1300/1500	340	7.5	20
		254/22°	10	115	50/60	0.42/0.41	30/28	1300/1500	441	8.7	20
83-2010 A2		230/22°	10	230	50/60	0.25/0.24	35/34	1300/1500	340	7.5	20
		254/22°	10	230	50/60	0.25/0.24	35/34	1300/1500	441	8.7	20



83 x 83 x 30 mm



83-4025 A2 Y		254/28°	25	230	50/60	0.50/0.47	65/67	1300/1450	595	10	10
		254/34°	25	230	50/60	0.52/0.50	73/75	1250/1300	700	11.5	10
		300/28°	25	230	50/60	0.55/0.50	73/75	1200/1250	900	13	10
83-4025 B2 Y		254/28°	25	230	50/60	0.50/0.47	65/67	1300/1450	595	10	10
		254/34°	25	230	50/60	0.52/0.50	73/75	1250/1300	700	11.5	10
		300/28°	25	230	50/60	0.55/0.50	73/75	1200/1250	900	13	10