

Products

Model No.	Bearing Sleeve	Rating Voltage (VAC)	Rated Current (Amp)	Power Consumption (W)	Speed (RPM)	Air Flow (CFM)	Static Pressure (mm H2O)	Noise (dBA)	Box Pkg. (Pcs)
REC	Ball								



40 x 40 x 12 mm

4012 A12 M		12	0.05	0.60	5100	7.5	3.8	23	100
------------	--	----	------	------	------	-----	-----	----	-----



60 x 60 x 25 mm

6025 A12 M		12	0.09	1.08	3800	20	3.8	27	90
6025 B12 M		12	0.09	1.08	3900	20	4.0	27	90
6025 A24 M		24	0.05	1.20	3800	19	3.8	27	90
6025 B24 M		24	0.05	1.20	3900	19	4.0	27	90



80 x 80 x 25 mm

8025 A12 M		12	0.13	1.56	2700	37	4.0	31	90
8025 B12 M		12	0.13	1.56	27800	37	4.0	31	90
8025 A24 M		24	0.08	1.92	2700	36	4.0	31	90
8025 B24 M		24	0.08	1.92	2800	36	4.0	31	90



92 x 92 x 25 mm

9225 A12 M		12	0.14	1.68	2600	46	3.5	29	40
9225 B12 M		12	0.14	1.68	2700	46	3.8	29	40
9225 A24 M		24	0.08	1.92	2600	44	3.5	29	40
9225 B24 M		24	0.08	1.92	2700	44	3.8	29	40



120 x 120 x 38 mm

12038 A12 M		12	0.35	4.20	2700	97	6.8	35	40
12038 B12 M		12	0.35	4.20	2800	98	6.8	35	40
12038 A24 M		24	0.20	4.80	2700	97	6.8	35	40
12038 B24 M		24	0.20	4.80	2800	98	6.8	35	40
12038 A48 M		48	0.12	5.76	2700	97	6.8	35	40
12038 A48 M		48	0.12	5.76	2800	98	6.8	35	40



172 x 150 x 51 mm

17251 B24 M		24	1.2	28.8	3600	300	22	60	20
----------------	--	----	-----	------	------	-----	----	----	----



220 x 60 mm

28025 A1 M W		24	1.5	36	3000	450	28	60	10
-----------------	--	----	-----	----	------	-----	----	----	----